

D930F

TEL: +46 070-536 3939 WEB: www.kelberg.se

KEL-BERG **MODEL KEL-BERG 3-AXLE FLATBED** TRAILER 7,500 MM

SPECIFICATION FOR D930F

KEL-BERG 3-AXLE FLATBED TRAILER 7,500 MM

WEIGHTS & DIMENSIONS:

Total length Body length Drawbar length Front overhang Rear overhang Coupling height Width Loading height Centre distance 9.580 mm 7.500 mm 2.000 - 3.000 mm 2.445 mm 2.245 mm 650 mm 2.540 mm 900 mm 2.720 mm

Speed Axle pressure Total weight Service weight **90 km/h** 30.000 kg 25.000 kg 5.300 kg

CHASSIS:

Made with heavy duty main frame, welded steel construction with 57mm sliding drawbar.

AXLES:

- 3 x 9 tonne SAF axles with drum brakes
- 1st & 3rd axle liftable, operable from cab or automatically
- Air suspension with level valve manoeuvrable front and rear.
- With ABS, EBS













PAGE: 2

WWW.KELBERG.SE | +46 070-536 3939 | 253 68, HELSINGBORG

Whilst every effort has been made to ensure that the information in this specification sheet is accurate, some errors may occur. It is important that you do not rely solely on this information, but that you check with your dealer any items that you believe will affect your decision to purchase this vehicle. Kel-Berg Trailers Sverige AB, accepts no responsibility for loss or damage resulting from incorrect or misleading information. This specification is for guidance only and does not constitute an offer of sale or warranty of the specification of this vehicle. All specifications are subject to change without notice and/or verification. EQOE.

SPECIFICATION FOR D930F

KEL-BERG 3-AXLE FLATBED TRAILER 7,500 MM

BODY:

- Heavy-duty, welded, high-strength steel construction
- 8 pairs of 2.5T anchor points in edge rope
- 3 pairs of LAXO sleeves in edge rope
- 3 pairs of LAXO sleeves in the centre
- 4 ladders
- Front trunk height 1.200 mm
- LAXO sleeves for 20' container
- Edge line of bent steel plate
- 3 battens each side 600mm with Kinnegrip posts K20
- Rear doors 600mm with Kinnegrip posts K20
- Hardwood bottom 30 mm

WHEELS:

• 8 x 265/70R19.5 mounted on steel rim with M+S tyres

BRAKES:

- 2-circuit compressed air system with EBS and ABS,
- Spring brake bells for parking brake
- 1 duomatic red/yellow

ELECTRICAL SYSTEM:

- 24 Volts according to current regulations
- 2 x rear multi-chamber lamps
- Side position lamps of diode type
- 2 x halogen rear position lamps













PAGE: 3

WWW.KELBERG.SE | +46 070-536 3939 | 253 68, HELSINGBORG

Whilst every effort has been made to ensure that the information in this specification sheet is accurate, some errors may occur. It is important that you do not rely solely on this information, but that you check with your dealer any items that you believe will affect your decision to purchase this vehicle. Kel-Berg Trailers Sverige AB. accepts no responsibility for loss or damage resulting from incorrect or misleading information. This specification is for guidance only and does not constitute an offer of sale or warranty of the specification of this vehicle. All specifications are subject to change without notice and/or verification FAOF

SPECIFICATION FOR D930F

KEL-BERG 3-AXLE FLATBED TRAILER 7,500 MM

ELECTRICAL CONNECTORS:

1 x 14-pin connector for lighting

PAINTING:

- 3 coat basecoat with zinc primer
- 2-component surface coating
- Colour: RAL 1042 chassis grey

OTHER:

- Red/white reflective plates(ECE70) rear
- Yellow retro-reflective (ECE104) contour markings on sides and rear
- Mudguards with anti-spray
- 1 stainless steel toolbox between 1a & 2a axle
- 1 large Kel-Berg rear mudguard

OPTIONS:

• Dura Bright aluminium wheels

PAGE: 4

WWW.KELBERG.SE | +46 070-536 3939 | 253 68, HELSINGBORG

Whilst every effort has been made to ensure that the information in this specification sheet is accurate, some errors may occur. It is important that you do not rely solely on this information, but that you check with your dealer any items that you believe will affect your decision to purchase this vehicle. Kel-Berg Trailers Sverige AB, accepts no responsibility for loss or damage resulting from incorrect or misleading information. This specification is for guidance only and does not constitute an offer of sale or warranty of the specification of this vehicle. All specifications are subject to change without notice and/or verification. E&OE