



MODEL
T560K

KEL-BERG 4-AXLE 38T DRAWBAR
TIPPER TRAILER 30 M³

SPECIFICATION FOR T560K

KEL-BERG 4-AXLE 38T DRAWBAR TIPPER TRAILER 30 M³

WEIGHTS & MEASURES:

Total length	13,380 / 15,080 / 15,600 mm
Drawbar length	3,200 / 4,900 / 5,400 mm
Front overhang	770 mm
Rear overhang	1,350 mm
Coupling height	650 mm
Width	2,550 mm
Axle distance	1,310 / 4,940 / 1,810 mm

TRAILER DIMENSIONS:

Internal length	8,900 mm
Internal width	2,440 mm
Height inside	1,350 mm
Cubic Capacity	30
Tipping angle	46 degrees

Speed	90 km/h
Front axle pressure	18,000 kg
Rear axle load	20,000 kg
Total weight	38,000 kg
Service weight	7,000 kg

CHASSIS:

Made of heavy duty main frame, welded steel construction with Trako pulls.



SPECIFICATION FOR T560K

KEL-BERG 4-AXLE 38T DRAWBAR TIPPER TRAILER 30 M³

BODY:

Aluminium body
Approx. 30 m³
7mm bottom
5mm sides
Tipping cylinder Penta - MAX 170 Bar

AXLES:

2 x 9ton BPW axles with front disc brakes
2 x 10ton BPW axles with rear disc brakes
Front and rear air suspension with level valve control.
With ABS, EBS
4th axle liftable, manoeuvrable from cab (Pin 10)

WHEELS:

8 pcs 385/65R22.5 mounted on Aluminium rims M+S

BRAKING:

2-circuit compressed air system with EBS and ABS,
Spring brake bells for parking brake
1 pc duomatic red/yellow

ELECTRICAL SYSTEM:

24 Volts according to current regulations
3 x 3 multi-chamber rear lights
6 LED work lights
2 work lights in the tipping bucket



SPECIFICATION FOR T560K

KEL-BERG 4-AXLE 38T DRAWBAR TIPPER TRAILER 30 M³

ELECTRICAL CONNECTORS:

1 x 14-pin connector for lighting

PAINTING:

Chassis colour

Colour of tipper box:

OTHER:

Rear reflective signs (ECE70)

Red/white contour markings sides and rear

Fenders with anti-spray

2 pcs rear flashing lights - active with reverse light

1 large Kelberg rear mudguard.

Plastic on rear underrun

Spring on towbar

COSTED OPTIONAL EXTRAS:

Flip top pneumatic canopy

With remote control

Canopy colour: any RAL

Plastic in bottom and sides

